




FLEXSTEEL® 250 STEAM

PRODUCT INFORMATION**APPLICATION:**

For cleaning, heat control, fire prevention, pumping, thawing, blow-out service, steam pumps and hoists in open-end or permanent installation operations. It is used in refineries, shipyards, chemical plants, steel mills, foundries and heavy industrial applications where high strength is required and where severe environmental conditions are encountered.

CONSTRUCTION:

Tube: Pyrosyn® synthetic rubber
Reinforcement: Braided steel wire (3/4" and 1" have 2 steel wire braids)
Cover: Black or Red Pyrosyn, smooth finish, pin-pricked

TEMPERATURE:

0°F to 450°F (-18°C to 232°C)

PACKAGING:

Reels or 50' cut lengths (1/2"–4' per box, 3/4"–3' per box, 1"–2' per box)

BRANDING:

Example: Goodyear® Flexsteel® 250 Steam (DC) Drain after using. Made in USA.

COUPLINGS:

Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

NON-STOCK/SIZES:

Refer to page 311 for special production run minimum requirements.

PRODUCT CODE:

539-070 (black) 539-076 (red)

ID	NOM. OD			MAX. WP			WEIGHT	
	inch	mm	psi	Mpa	lbs/ft	lbs/ft		
1/2*	1.06	26.9	250	1.72	0.42	0.63		
3/4	1.28	32.8	250	1.72	0.49	0.73		
1**	1.63	41.4	250	1.72	0.91	1.35		

FLEXSTEEL® 250 CB STEAM

PRODUCT INFORMATION**APPLICATION:**

Used for cleaning, heat control, fire prevention, pumping, thawing, blowout service, steam pumps and hoists in open-end or permanent installation operations. It is used in refineries, shipyards, chemical plants, steel mills, foundries and heavy industrial applications where high strength is required and where severe environmental conditions are encountered.

CONSTRUCTION:

Tube: Chlorobutyl synthetic rubber
Reinforcement: Braided steel wire (3/4" and higher have 2 steel wire braids)
Cover: Red or black Pyrosyn® synthetic rubber
TEMPERATURE: 0°F to 425°F (-18°C to 218°C)

BRANDING:

Example (smooth cover): Goodyear® 250 Steam (CB)-(DC) Drain after using. Made in USA. Example (wrapped cover): Goodyear® Ultrabraid Flexsteel® 250 CB Steam WP. 1.75Mpsa/250 PSI WP. Service Temp. 220°C/425°F Drain after using. Made in USA.

Smooth cover:

Reels or 50' cut lengths (3/4"–3'/box, 1"–2'/box)
 1/2" Four 50' exact length/box
 3/4"–1" Three 50' exact length/box
 1 1/4"–2" One 50' exact length/box

Wrapped cover:

Contact fitting manufacturer for proper fitting recommendation and coupling procedure
 Refer to page 311 for special production run minimum requirements

NON-STOCK/SIZES:

Refer to page 311 for special production run minimum requirements

SF-SMOOTH FINISH

ORDER CODES:539-370 (black) 539-376 (red)

ID	NOM. OD			MAX. WP			WEIGHT	
	inch	mm	psi	Mpa	lbs/ft	lbs/ft		
1/2	1.06	26.9	250	1.72	0.40	0.60		
3/4	1.28	32.5	250	1.72	0.56	0.86		
1	1.63	41.4	250	1.72	0.84	1.25		

WF-WRAPPED FINISH

ORDER CODES:539-370 (black) 539-376 (red)

ID	NOM. OD			MAX. WP			WEIGHT	
	inch	mm	psi	Mpa	lbs/ft	lbs/ft		
1/2	1.00	25.4	250	1.72	0.40	0.60		
3/4	1.31	33.3	250	1.72	0.64	0.95		
1	1.56	39.6	250	1.72	0.77	1.15		
1 1/4	1.75	44.5	250	1.72	1.06	1.58		
1 1/2	2.00	50.8	250	1.72	1.42	2.11		
2	2.50	63.5	250	1.72	1.71	2.54		