

**HORIZON®**

PRODUCT INFORMATION



PRODUCT INFORMATION

BS 2050/ISO 8031 Anti-Static Air Hose**APPLICATION:**

An economical air and water hose, Horizon® is for a wide range of industrial, construction and agricultural applications. Available in 200, 250, and 300 PSI working pressures.

APPLICATION:

An economical air hose with excellent ozone resistance for use in applications where the hose assembly needs to be anti-static meeting the requirements of BS 2050/ ISO 8031 R < 106 Ω

CONSTRUCTION:

Tube: Versigard® synthetic rubber, RMA Class C (Limited Oil Resistance)
Reinforcement: Spiral synthetic yarn, 2" is braided
Cover: Black, Red, Yellow, Green or Blue Versigard® synthetic rubber

CONSTRUCTION:

Tube: Versigard™ synthetic rubber, statically conducting to BS2050 / ISO 8031
Reinforcement: Spiral of synthetic yarn.
Cover: Versigard synthetic Rubber™

TEMPERATURE:

-40°F to 190°F (-40°C to 88°C)

TEMPERATURE:

-40°C/+88°C (-40°F/to +190°F)

PACKAGING:

3/16"-3/4" 500' reels, maximum 3 pieces, 50' increments
 1" 450' reels, maximum 3 pieces, 50' increments
 1 1/4" 400' reels, maximum 3 pieces, 50' increments
 1 1/2" 300' reels, maximum 3 pieces, 50' increments
 2" 200' cartons, maximum 3 pieces, 50' increments
 Coupled assemblies available in 1/4", 3/8", 1/2", and 3/4" in red

BRANDING:

GOODYEAR 3/4" (19.1mm) RIG AIR BS 2050 WP 20 Bar
 CONDUCTIVE R < 106 Ω ISO 8031.

COUPLINGS:

Contact fitting manufacturer for proper fitting recommendation and coupling procedure.
 Example: 1/2" Horizon® Goodyear® 300 psi WP
 For special production run minimum requirements, see Appendix D.
 See next page.

RECOMMENDED FITTINGS:

Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

TESTING/STANDARDS:

All hoses tested to BS 2050 / ISO 8031.

ORDER CODE:

569-622

NON-STOCK/SIZES:

See next page.

NON-STOCK/SIZES:

See next page.

mm	inch	mm	bar	mm	lbs/ft
10.0	3/8	17.6	20	60	0.157
13.0	1/2	21.6	20	78	0.228
16.0	5/8	24.8	20	115	0.278
19.0	3/4	28.6	20	135	0.355
25.4	1	36.8	20	150	0.535