




RIG SUPPLY HW

PRODUCT INFORMATION

RIG SUPPLY SW

PRODUCT INFORMATION**APPLICATION:**

Heavy duty high performance oil suction and discharge hose for the transfer of oil and petroleum base products including bulk supply of diesel oil from supply vessels to off-shore platforms and drilling rigs.

CONSTRUCTION:

Tube: Black, oil and aromatics resistant Chemigum® (Nitrile) synthetic rubber
Reinforcement: Spiral plied (4) synthetic fabric and 2 Helix wires with excellent crush and kink resistance

Cover:

Black, oil, heat, ozone and sea water resistant Wingprene® (Neoprene) synthetic rubber and wrapped finish

TEMPERATURE:

-30°C to 93°C

BRANDING:

GOODYEAR RIG SUPPLY SW WP20BAR BP60BAR -M

PACKAGING:

18.3m coils (available in other lengths up to max 120m)

ORDER CODE:

543-297 (3 - 6")
541-297 (8 - 10")

APPLICATION:

Heavy duty high performance discharge hose for the transfer of oil and petroleum base products including bulk supply of diesel oil from supply vessels to off-shore platforms and drilling rigs.

CONSTRUCTION:

Tube: Black, oil and aromatics resistant Chemigum® (Nitrile) synthetic rubber
Reinforcement: Spiral plied (4) synthetic fabric and anti-static wire

Cover:

Black, oil, heat, ozone and sea water resistant Wingprene® (Neoprene) synthetic rubber and wrapped finish

TEMPERATURE:

-30°C to 93°C

GOODYEAR RIG SUPPLY SW BRANDING:

GOODYEAR RIG SUPPLY SW WP20BAR BP60BAR -M

PACKAGING:

18.3m coils (available in other lengths up to max 120m)

ORDER CODE:

543-295 (3 - 6")
541-295 (8 - 10")

inch	mm	inch	mm	bar	psi	mm	kg/m
3	76	3.58	91	20	290	450	3,35
4	102	4.61	117	20	290	620	4,75
5	127	5.71	145	20	290	760	7,09
6	152	6.77	172	20	290	920	8,54
8	203	8.90	226	20	290	1230	10,15
10	254	11.14	283	20	290	2540	14,50

inch	mm	inch	mm	bar	psi	mm	kg/m
3	76	3.58	91	20	290	600	2,850
4	102	4.61	117	20	290	800	3,995
5	127	5.71	145	20	290	1020	4,990
6	152	6.77	172	20	290	1220	5,200
8	203	8.90	226	20	290	1620	8,050
10	254	11.14	283	20	290	2040	23,600